

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

Claim Amendments

1. (Currently Amended) An apparatus for joining a plurality of ~~cylindrical~~ rod sections together, comprising:

a plug assembly fixedly engaged to a first rod proximate end and having a plurality of first splines and a plurality of first connectors;

a socket assembly fixedly engaged to a second rod distal end and having a plurality of receptacles adapted to receive the plurality of splines and a plurality of second connectors of the plug assembly;

a securing device for securing the plug assembly to the socket assembly;

wherein the plug assembly may be joined to and the socket assembly by the securing device may be joined in N a plurality of orientations-where N is equal to the number of splines so that, in each of the plurality of orientations, when the plurality of splines in the plug assembly mate with the plurality of receptacles in the socket assembly, the plurality of first connectors engage the plurality of second connectors.

2. (Original) The apparatus of claim 1, wherein the plurality of splines further comprises a center spline and a plurality of outer splines of equal dimensions, the outer splines sharing a common longitudinal axis with the center spline and having symmetry about the common longitudinal axis, and where N is equal to the number of outer splines.

3. (Original) The apparatus of claim 1, wherein the securing device is a coupling collar adapted for connecting it to the plug assembly and the socket assembly, the coupling collar initially engaged with the plug assembly.

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

4. (Original) The apparatus of claim 1, wherein the plug assembly further comprises fine threads.
5. (Original) The apparatus of claim 1, wherein the socket assembly further comprises coarse threads.
6. (Original) The apparatus of claim 5, wherein the threads of the socket assembly are tapered.
7. (Currently Amended) The apparatus of claim 1, wherein the ~~cylindrical~~ rod sections are connectable in two distinct orientations.
8. (Currently Amended) The apparatus of claim 1, wherein the cylindrical-rod sections are connectable in three distinct orientations.
9. (Currently Amended) The apparatus of claim 1, wherein the ~~cylindrical~~ rod sections are connectable in four or more distinct orientations.
10. (Original) The apparatus of claim 1, further comprising at least one conduit containing a wire adapted to carry an electrical current.
11. (Original) The apparatus of claim 1, further comprising at least one conduit containing material adapted to carry an optical signal.
12. (Cancelled) The apparatus of claim 1 wherein the cylindrical sections are tubing.
13. (Cancelled) The apparatus of claim 1 wherein the cylindrical sections are pipe.
14. (Cancelled) The apparatus of claim 1 wherein the cylindrical sections are casing.
15. (Cancelled) The apparatus of claim 1 wherein the cylindrical sections are used to produce hydrocarbons from a well bore.
16. (Cancelled) The apparatus of claim 1 wherein the cylindrical sections are used to produce water from a well bore.

Attorney Docket No. AHUG.015

Serial No. 10/671,141

Preliminary Amendment

17. (Original) The apparatus of claim 1 wherein the cylindrical sections are connectable in a plurality of distinct orientations.

18. (Currently Amended) An apparatus for providing power to a subterranean environment, comprising:

~~a drilling~~ an assembly containing a plurality of cylindrical rod sections;

a plurality of cylindrical joints for connecting the plurality of ~~cylindrical rod~~ sections together, ~~the each cylindrical joints joint~~ comprising:

a plug assembly fixedly engaged to a rod proximate end and having a plurality of splines;

a socket assembly fixedly engaged to a rod distal end and having a plurality of receptacles, the plurality of receptacles of one rod section's socket assembly adapted to receive the plurality of splines of another rod section's ~~the~~ plug assembly;

~~at least one~~ a plurality of conduit transmission means running the length of the apparatus;

a securing device for securing the plug assembly of one rod section to the socket assembly of another rod section; and

wherein the plug assembly of one rod section and the socket assembly of another rod section may be joined in N orientations where N is equal to the number of splines;

and

wherein the plurality of transmission means are aligned for connectivity when

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

the plug assembly of one rod section is joined to the socket assembly of another rod section.

19. (Original) The apparatus of claim 18, wherein the plurality of splines further comprises a center spline and a plurality of outer splines of equal dimensions, the outer splines sharing a common longitudinal axis with the center spline and having symmetry about the common longitudinal axis, and wherein N is equal to the number of outer splines.

20. (Original) The apparatus of claim 19, wherein the securing device is a coupling collar adapted for connection to the plug assembly and the socket assembly, the coupling collar initially engaged with the plug assembly.

21. (Original) The apparatus of claim 19, wherein the plug assembly further comprises fine threads.

22. (Original) The apparatus of claim 19, wherein the socket assembly further comprises coarse threads.

23. (Original) The apparatus of claim 22, wherein the threads of the socket assembly are tapered.

24. (Currently Amended) The apparatus of claim 19, wherein the cylindrical rod sections are connectable in two distinct orientations.

25. (Currently Amended) The apparatus of claim 19, wherein the cylindrical rod sections are connectable in three distinct orientations.

26. (Currently Amended) The apparatus of claim 19, wherein the cylindrical rod sections are connectable in four or more distinct orientations.

Attorney Docket No. AHUG.015

Serial No. 10/671,141

Preliminary Amendment

27. (Original) The apparatus of claim 19, further comprising at least one conduit containing a wire adapted to carry an electrical current.

28. (Original) The apparatus of claim 19, further comprising at least one conduit containing material adapted to carry an optical signal.

29. (Cancelled) The apparatus of claim 19 wherein the cylindrical sections are tubing.

30. (Cancelled) The apparatus of claim 19 wherein the cylindrical sections are pipe.

31. (Cancelled) The apparatus of claim 19 wherein the cylindrical sections are casing.

32. (Cancelled) The apparatus of claim 19 wherein the cylindrical sections are used to produce hydrocarbons from a well bore.

33. (Cancelled) The apparatus of claim 19 wherein the cylindrical sections are used to produce water from a well bore.

34. (Original) The apparatus of claim 19 wherein the cylindrical sections are connectable in a plurality of orientations.

35. (Currently Amended) A method of using a cylindrical joint to join two ~~cylindrical rod~~ sections together, comprising:

using a first ~~cylindrical rod~~ section with a proximate end having a plug assembly attached and a second ~~cylindrical rod~~ section with a distal end having a socket assembly attached, positioning the first ~~cylindrical rod~~ section coaxially with the second ~~cylindrical rod~~ section;

aligning the first ~~cylindrical rod~~ section with the second ~~cylindrical rod~~ section;

engaging the plug assembly of the first ~~cylindrical rod~~ section into the socket assembly of the second ~~cylindrical rod~~ section; and

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

securing the first cylindrical rod section to the second cylindrical rod section.

36. (Currently Amended) The method of claim 35 wherein the positioning step further comprises: positioning the first cylindrical rod section coaxially with the second cylindrical rod section such that the proximate end of the first cylindrical rod section is in close proximity with the distal end of the second cylindrical rod section.

37. (Currently Amended) The method of claim 35 wherein the positioning step further comprises:

aligning the first cylindrical rod section with the second cylindrical rod section by rotating one or both cylindrical rod sections such that the plug assembly outer splines of the first cylindrical rod section are positioned to properly mate with the receptacle receptacles in the socket assembly of the second cylindrical rod section.

38. (Currently Amended) The method of claim 35 wherein the first cylindrical rod section is vertically above the second cylindrical rod section.

39. (Currently Amended) The method of claim 35 wherein a pair of electrical connectors are electrically coupled when the plug assembly of the first cylindrical rod section is inserted into the socket assembly of the second cylindrical rod section.

40. (Currently Amended) The method of claim 35 wherein a pair of optical connectors are optically coupled when the plug assembly of the first cylindrical rod section is inserted into the socket assembly of the second cylindrical rod section.

41. (Currently Amended) The method of claim 35 wherein the coupling collar of the first cylindrical rod section is used to secure the first cylindrical rod section to the second cylindrical rod section.

42. (Cancelled) The method of claim 35 wherein the cylindrical sections are tubing.

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

43. ~~(Cancelled)~~ The method of claim 35 wherein the cylindrical sections are pipe.
44. ~~(Cancelled)~~ The method of claim 35 wherein the cylindrical sections are casing.
45. ~~(Cancelled)~~ The method of claim 35 wherein the cylindrical sections are used to produce hydrocarbons from a well bore.
46. ~~(Cancelled)~~ The method of claim 35 wherein the cylindrical sections are used to produce water from a well bore.

47. ~~(Currently Amended)~~ In a drill string apparatus of the type comprising a plurality of cylindricalrod sections arranged in end to end relation from a location above the ground to a lower location adjacent to an orientable tool connected to a bottom end of the drill string apparatus and wherein the adjacent ends of the cylindricalrod sections are connected to each other to form a plurality of spaced cylindricalrod joints extending downwardly from the ground to the tool, wherein each cylindricalrod section is provided with a lower end having a downwardly projecting extension plurality of splines and an upper end having a complementary recess plurality of receptacles which is in alignment with and corresponds with the downwardly projecting extension plurality of splines on the lower end of the same cylindricalrod section, and wherein each cylindricalrod joint comprises an upper cylindricalrod section having its downwardly projecting extensions plurality of splines received in the corresponding recess plurality of receptacles in the next adjacent lower cylindricalrod section and wherein the extensions plurality of splines and the recesses the plurality of receptacles can fit together in more than one orientation, wherein the adjacent ends of the sections are threaded and wherein an internally threaded collar is received over the threaded ends to hold the sections of each cylindricalrod joint

Attorney Docket No. AIIUG.015

Serial No. 10/671,141

Preliminary Amendment

securely together, and wherein a plurality of connectors are aligned for connectivity when the splines of the upper rod section are received in the corresponding receptacles in the next adjacent rod section.

48. (Currently Amended) A ~~cylindrical~~rod joint as set forth in claim 47 wherein the upper ~~cylindrical~~rod section and lower ~~cylindrical~~rod section are provided with keyways which are symmetrically related with respect to the longitudinal axis of the drill string and wherein keys are affixed to the keyways of the upper drill section and are adapted to fit into the keyways of the lower ~~cylindrical~~rod section.

49. (Currently Amended) A ~~cylindrical~~rod joint as set forth in claim 47 wherein the upper ~~cylindrical~~rod section is provided with at least three downwardly extending legs which are symmetrically arranged with respect to the longitudinal axis of the drill string and wherein the lower ~~cylindrical~~rod section is provided with a corresponding number of recesses arranged so as to receive the legs of the upper ~~cylindrical~~rod section.

50. (Currently Amended) An apparatus for connecting a plurality of ~~cylindrical~~rod sections together comprising:

a first ~~cylindrical~~rod section;

a second ~~cylindrical~~rod section removably connected to the first ~~cylindrical~~rod section; and

wherein the first ~~cylindrical~~rod section and the second ~~cylindrical~~rod section are connectable in a plurality of distinct orientations so that when connected in one of the plurality of distinct orientations a first transmission means of the first rod section is engaged with a second transmission means in the second rod section.

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

51. (Currently Amended) The apparatus of claim 50 wherein the connection between the first ~~cylindrical~~rod section and the second ~~cylindrical~~rod section comprises: a means for connecting the first ~~cylindrical~~rod section to the second ~~cylindrical~~rod section in a plurality of distinct orientations.

52. (Currently Amended) The apparatus of claim 50 wherein the connection between the first ~~cylindrical~~rod section and the second ~~cylindrical~~rod section comprises:

a plug assembly having a plurality of splines affixed to the first ~~cylindrical~~rod section;

a socket assembly having a plurality of receptacles adapted to receive the plurality of splines of the plug assembly, the socket assembly being affixed to the second ~~cylindrical~~rod section; and

a securing device for securing the plug assembly to the socket assembly.

53. (Original) The apparatus of claim 52, wherein the securing device is a coupling collar adapted for connection to the plug assembly and the socket assembly, the coupling collar initially engaged with the plug assembly.

54. (Original) The apparatus of claim 53, wherein the plug assembly further comprises fine threads.

55. (Original) The apparatus of claim 53, wherein the socket assembly further comprises coarse threads.

56. (Original) The apparatus of claim 55, wherein the threads of the socket assembly are tapered.

57. (Currently Amended) The apparatus of claim 52, wherein the ~~cylindrical~~rod sections are connectable in two distinct orientations.

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment

58. (Currently Amended) The apparatus of claim 52, wherein the cylindrical rod sections are connectable in three distinct orientations.

59. (Currently Amended) The apparatus of claim 52, wherein the cylindrical rod sections are connectable in four or more distinct orientations.

60. (Original) The apparatus of claim 52, further comprising at least one conduit containing a wire adapted to carry an electrical current.

61. (Original) The apparatus of claim 52, further comprising at least one conduit containing material adapted to carry an optical signal.

62. (Cancelled) ~~The apparatus of claim 52 wherein the cylindrical sections are tubing.~~

63. (Cancelled) ~~The apparatus of claim 52 wherein the cylindrical sections are pipe.~~

64. (Cancelled) ~~The apparatus of claim 52 wherein the cylindrical sections are casing.~~

65. (Cancelled) ~~The apparatus of claim 52 wherein the cylindrical sections are used to produce hydrocarbons from a well bore.~~

66. (Cancelled) ~~The apparatus of claim 52 wherein the cylindrical sections are used to produce water from a well bore.~~

67. (Cancelled) ~~The apparatus of claim 1 wherein the cylindrical sections are rods.~~


68. (Cancelled) ~~The apparatus of claim 19 wherein the cylindrical sections are rods.~~

69. (Cancelled) ~~The method of claim 35 wherein the cylindrical sections are rods.~~

70. (Cancelled) ~~The apparatus of claim 52 wherein the cylindrical sections are rods.~~

Attorney Docket No. AHUG.015
Serial No. 10/671,141
Preliminary Amendment


Respectfully submitted,


Rudolf O. Siegesmund
Registration No. 37,720
Suite 2000
4627 N. Central Expressway
Dallas, Texas 75205-4017
214-528-2407
FAX 214-528-2434
Attorney for Applicant

Certificate of Transmission

I hereby certify that this correspondence is being facsimile transmitted to the Patent and Trademark Office (Fax No. (703) 872-9306).

On 6/28/2005
Date


Rudolf O. Siegesmund